

## 40V N-Channel Enhancement Mode MOSFET

### Description

The NP4030D6 uses advanced trench technology that is uniquely optimized to provide the most efficient high frequency switching performance. Both conduction and switching power losses are minimized due to an extremely low combination of  $R_{DS(ON)}$  and  $Q_g$ . This device is ideal for high-frequency switching and synchronous rectification.

### General Features

- ◆  $V_{DS} = 40V$   $I_D = 30A$   
 $R_{DS(ON)}(\text{Typ.}) = 6.4m\Omega$  @  $V_{GS} = 10V$   
 $R_{DS(ON)}(\text{Typ.}) = 8.5m\Omega$  @  $V_{GS} = 4.5V$
- ◆ Excellent gate charge  $\times R_{DS(on)}$  product(FOM)
- ◆ Very low on-resistance  $R_{DS(on)}$
- ◆ 150 °C operating temperature
- ◆ 100% UIS tested


*100% UIS TESTED!*

*100%  $\Delta V_{ds}$  TESTED!*

### Application


- ◆ Synchronous Rectification in DC/DC and AC/DC Converters
- ◆ Industrial and Motor Drive applications

### Schematic diagram



### Marking and pin assignment

PDFN5\*6-8L-A



Top View

XXXXXX—Wafer Information

YYYYYY—Quality Code

Bottom View



### Ordering Information

Part Number	Storage Temperature	Package	Devices Per Reel
NP4030D6-G	-55°C to +150°C	PDFN5*6-8L-A	5000

### Absolute Maximum Ratings (TA=25°C unless otherwise noted)

parameter	symbol	limit	unit
Drain-source voltage	$V_{DS}$	40	V
Gate-source voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current TC=25°C	$I_D$	30	A
TC=70°C		24	
Pulsed Drain Current	$I_{DP}$	120	A
Avalanche energy( $T_j=25^\circ C$ , $V_{DD}=30V$ , $V_G=10V$ , $L=0.5mH$ , $R_g=25\Omega$ )	$E_{AS}$	120	mJ
Power Dissipation TC=25°C	$P_D$	37.5	W
TC=70°C		15	
Operating junction Temperature range	$T_j$	-55—150	°C

**Electrical Characteristics** (TA=25°C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
<b>Static Characteristics</b>						
Drain-source breakdown voltage	BV <sub>DSS</sub>	V <sub>GS</sub> =0V, I <sub>D</sub> =250μA	40	-	-	V
Zero gate voltage drain current	I <sub>DSS</sub>	V <sub>DS</sub> =40V, V <sub>GS</sub> =0V T <sub>J</sub> =85°C	-	-	1	μA
			-	-	5	
Gate Leakage Current	I <sub>GSS</sub>	V <sub>DS</sub> =0V, V <sub>GS</sub> =±20V	-	-	±100	nA
Gate threshold voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA	1.0	1.6	2.5	V
Drain-source on-state resistance	R <sub>DS(ON)</sub>	V <sub>GS</sub> =10V, I <sub>D</sub> =20A	-	6.4	7.5	mΩ
		V <sub>GS</sub> =4.5V, I <sub>D</sub> =15A		8	10	
Forward Transconductance	g <sub>FS</sub>	V <sub>DS</sub> =5V, I <sub>D</sub> =20A	-	47	-	S
<b>Diode Characteristics</b>						
Diode Forward Voltage	V <sub>SD</sub>	I <sub>SD</sub> =1A, V <sub>GS</sub> =0V	-	0.7	1.2	V
Diode Continuous Forward Current	I <sub>S</sub>		-	-	20	A
Reverse Recovery Time	t <sub>rr</sub>	T <sub>J</sub> = 25°C, I <sub>F</sub> = I <sub>S</sub> di/dt = 100A/μs	-	31	-	ns
Reverse Recovery Charge	Q <sub>rr</sub>		-	33	-	nC
<b>Dynamic Characteristics</b>						
Gate Resistance	R <sub>G</sub>	V <sub>GS</sub> =0V, V <sub>DS</sub> =0V, f=1MHz	-	3.6	5.4	Ω
Input capacitance	C <sub>ISS</sub>	V <sub>GS</sub> =0V, V <sub>DS</sub> =20V f=1.0MHz	-	1600	-	pF
Output capacitance	C <sub>OSS</sub>		-	320	-	
Reverse transfer capacitance	C <sub>RSS</sub>		-	100	-	
Turn-on delay time	t <sub>D(ON)</sub>	V <sub>GS</sub> =10V, V <sub>DS</sub> =20V, R <sub>L</sub> =1.5Ω, R <sub>G</sub> =3Ω	-	6.5	-	ns
Turn-on Rise time	tr		-	12.5	-	
Turn-off delay time	t <sub>D(OFF)</sub>		-	33	-	
Turn-off Fall time	t <sub>f</sub>		-	16	-	
Total gate charge	Q <sub>g</sub>	V <sub>GS</sub> =10V, V <sub>DS</sub> =20V, I <sub>D</sub> =30A	-	22	-	nC
Gate-source charge	Q <sub>gs</sub>		-	4.3	-	
Gate-drain charge	Q <sub>gd</sub>		2	4.8	-	

**Thermal Characteristics**

Parameter	Symbol	Typ	Max	Unit
Maximum Junction-to-Ambient <sup>A</sup>	≤ 10s	R <sub>θJA</sub>	12	20
Maximum Junction-to-Ambient <sup>A</sup>	Steady-State		33	50
Maximum Junction-to-Lead <sup>B</sup>	Steady-State		2.4	2.9


A: The value of R<sub>θJA</sub> is measured with the device mounted on 1in 2 FR-4 board with 2oz. Copper, in a still air environment with T A=25°C. The value in any given application depends on the user's specific board design. The current rating is based on the t ≤ 10s thermal resistance rating.

B: The R<sub>θJA</sub> is the sum of the thermal impedance from junction to lead R<sub>θJL</sub> and lead to ambient.


## Package Information

- PDFN5\*6-8L-A


Top View



Bottom View



Side View



SYMBOLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.870	0.900	0.930	0.034	0.035	0.036
A3	0.152REF.			0.006REF.		
D	4.944	5.020	5.096	0.195	0.198	0.201
E	5.974	6.050	6.126	0.235	0.238	0.241
D1	3.910	4.010	4.110	0.154	0.158	0.162
E1	3.375	3.475	3.575	0.133	0.137	0.141
D2	4.870	4.900	4.930	0.192	0.193	0.194
E2	5.720	5.750	5.780	0.226	0.227	0.228
k	1.190	1.290	1.390	0.047	0.051	0.055
b	0.350	0.380	0.410	0.014	0.015	0.016
e	1.270TYP.			0.050TYP.		
L	0.559	0.635	0.711	0.022	0.025	0.028
L1	0.424	0.500	0.576	0.017	0.020	0.023
H	0.574	0.650	0.726	0.023	0.026	0.029
θ	10°	11°	12°	10°	11°	12°
Φ	1.150	1.200	1.250	0.045	0.047	0.049